



## FRAME COMPONENTS

**RAFTERS:** Welded truss construction with 3-inch **12 gauge** top and bottom chords.  
**RAFTERS AND PURLINS:** Straight and/or "X" bracing configured to application.  
**RAFTER SPACING:** Offered in 8-foot, 10-foot, and 14-foot truss spacing depending on local codes.  
**PONY WALL MODELS:** Designed to be set on wood, concrete, or steel, with standard pivot bracket. Walls must be at least 24-inches high to allow for tensioning.  
**Note:** also available in flush mount and ground mounted units with wider interior clearance.  
**Included:** assembly bolts, lashing winches with mounting brackets.  
**Not included:** posts, rub rail, or concrete anchors.

## FABRIC COVER

**FABRIC:** 12.5 oz tear resistant high density polyethylene with reinforced corners and pockets.  
**COLORS:** White, Blue, Green, Red, Tan, Silver, Frost/translucent.  
Available as solid colors (some colors may be up charged), with colored canastoga ends, or stripes.  
**TENSIONING:** Pipe and 2" lashing winch at each truss.  
Standard end tension kit with ratchets spaced at 36"; high tension kit available.

## AVAILABLE OPTIONS

**END WALLS:** Steel uprights with fabric cover; pipe and 2" lashing winch tensioning.  
**END WALL SUPPORTS:** Our standard uprights with tabs for customer supplied girts and skin.  
**HEADERS & DOORS:** Door headers available. Fabric roll-up doors available.  
**RIDGE VENTS:** 8X16 top vent holes, partial or entire length of building.  
**AWNING:** 5ft awning greatly extends weather protection for buildings with feed-bunks or open sides.  
**SIDE CURTAINS:** Roll-Up curtain to allow ventilation or wind protection. Electric curtain option available.